

PRODUCT CHARACTERISTICS

V_{DSS}	70V
$R_{DS(ON)}$ Typ(@ $V_{GS}=10V$)	5.2m Ω
Qg@typ	100nC
I_D	100A

APPLICATIONS

- * High efficiency switch mode power supplies
- * Electronic lamp ballasts based on half bridge
- * LED power supplies

FEATURE

- * High Switching Speed
- * Improved dv/dt capability

ORDER INFORMATION

Order Codes		Package	Packing
Halogen-Free	Halogen		
N/A	MOT100N07D	TO-252	2500 pieces/Tube


ABSOLUTE MAXIMUM RATINGS($T_A=25^{\circ}C$, unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	70	V
Gate-Source Voltage	V_{GSS}	± 20	V
Drain Current Continuous(@ $V_{GS}=10V, T_A=25^{\circ}C$)	I_D	100	A
Drain Current Continuous(@ $V_{GS}=10V, T_A=100^{\circ}C$)	I_D	70.7	A
Drain Current Pulsed	I_{DM}	400	A
Avalanche Energy *	E_{AS}	484	mJ
Power Dissipation	P_D	136	W
Junction Temperature	T_J	+150	$^{\circ}C$
Storage Temperature	T_{STG}	-55~ +150	$^{\circ}C$

THERMAL CHARACTERISTICS

Parameter	Symbol	Typ	Unit
Junction to Case	R_{thJC}	0.92	$^{\circ}C/W$

Note: * EAS condition: $T_J=25^{\circ}C, V_{DD}=40V, V_G=10V, L=0.5mH, R_g=25\Omega$



■ ELECTRICAL CHARACTERISTICS ($T_C=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain to Source Breakdown Voltage	V _{DSS}	V _{GS} =0V, I _D =250μA	70	-	-	V
Drain to Source Leakage Current	I _{DSS}	V _{DS} =70V, V _{GS} =0V	-	-	1	μA
Gate to Source Forward Leakage	I _{GSS(F)}	V _{DS} =0V, V _{GS} =+20V	-	-	100	nA
Gate to Source Reverse Leakage	I _{GSS(R)}	V _{DS} =0V, V _{GS} =-20V	-	-	-100	nA
On characteristics						
Drain to Source On-Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =20A	-	5.2	6.5	mΩ
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2	3	4	V
Dynamic characteristics						
Gate capacitance	R _g	V _{GS} =0V, V _{DS} =0V ,f=1.0MHz	-	0.75	-	Ω
Forward Transconductance	g _{fs}	V _{DS} =5V, I _D =5A	-	18	-	S
Input Capacitance	C _{iss}	V _{DS} =25V, V _{GS} =0V f=1.0MHz	-	4800	-	pF
Output Capacitance	C _{oss}		-	270	-	pF
Reverse Transfer Capacitance	C _{rss}		-	260	-	pF
Resistive Switching Characteristics						
Turn-on Delay Time	t _{d(ON)}	I _D =20 A, V _{DS} =30V R _G =2.5 Ω ,V _{GS} =10V	-	17	-	ns
Rise Time	t _r		-	11	-	ns
Turn-off Delay Time	t _{d(OFF)}		-	55	-	ns
Fall Time	t _f		-	15	-	ns
Total Gate Charge	Q _g	I _D =20 A, V _{DS} =30V V _{GS} =10V	-	100	-	nC
Gate to Source Charge	Q _{gs}		-	21	-	nC
Gate to Drain("Miller") Charge	Q _{gd}		-	30	-	nC
Source-Drain Diode Characteristics						
Continuous Source Current(Body Diode)	I _s		-	-	100	A
Maximum Pulsed Current(Body Diode)	I _{SM}		-	-	400	A
Diode Forward Voltage	V _{SD}	I _{SD} =1A, V _{GS} =0V	-	0.72	1.2	V
Reverse Recovery Time	t _{rr}	I _{SD} =20A, T _J =25°C	-	37	-	ns
Reverse Recovery Charge	Q _{rr}	di /dt=100A/μs	-	58	-	μC

■ TYPICAL CHARACTERISTICS




Figure 1: Output characteristics




Figure 2: Rdson-junction temperature




Figure 3: Transfer characteristics




Figure 4: Gate charge




Figure 5: Rdson-drain current




Figure 6: Source-drain diode forward

■ TYPICAL CHARACTERISTICS(Cont.)




Figure 7: Capacitance vs vds




Figure 9: Power de-rating




Figure 9: Safe operation area




Figure 10: Current de-rating

■ TO-252 PACKAGE OUTLINE DIMENSIONS

