
■ PRODUCT CHARACTERISTICS

V_{DSS}	100V
$R_{DS(ON)}$ Typ(@V_{GS}=10V)	16mΩ
$R_{DS(ON)}$ Typ(@V_{GS}=4.5V)	21mΩ
I_D	40A

Symbol



■ APPLICATIONS

* Electronic lamp ballasts based on half bridge
* Load Switching,Quick/Wirelss Charge.
* Motor Driving

■ FEATURE

* Low Gate Charge
* Pb-Free Lead Plating



3:Source



TO-252

■ ORDER INFORMATION

Order Codes		Package	Packing
Halogen-Free	Halogen		
N/A	MOT40N10D	TO-252	2500 pieces/Reel

■ ABSOLUTE MAXIMUM RATINGS(T_A=25°C,unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	40	V
Gate-Source Voltage	V_{GSS}	±20	V
Drain Current Continuous(@V_{GS}=10V,T_A=25°C)	I_D	40	A
Drain Current Continuous(@V_{GS}=10V,T_A=100°C)	I_D	25	A
Drain Current Pulsed	I_{DM}	160	A
Avalanche Energy *	E_{AS}	24	mJ
Power Dissipation	P_D	55	W
Junction Temperature	T_J	+150	°C
Storage Temperature	T_{STG}	-55~ +150	°C

■ THERMAL CHARACTERISTICS

Parameter	Symbol	Typ	Unit
Junction to Case	R_{thJC}	2.27	°C/W

Note: * EAS condition: T_J=25°C,V_{DD}=30V,V_G=10V ,L=0.5mH,R_g=25Ω

■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain to Source Breakdown Voltage	V_{DSS}	V_{GS}=0V,I_D=250μA	100	-	-	V
Drain to Source Leakage Current	I_{DSS}	V_{DS}=100V,V_{GS}=0V	-	-	1	μA
Gate to Source Forward Leakage	$I_{GSS(F)}$	V_{GS}=+20V,V_{DS}=0V	-	-	100	nA
Gate to Source Reverse Leakage	$I_{GSS(R)}$	V_{GS}=-20V ,V_{DS}=0V	-	-	-100	nA
On characteristics						
Drain to Source On-Resistance	$R_{DS(ON)}$	V_{GS}=10V,I_D=20A	-	16	20	mΩ
		V_{GS}=4.5V,I_D=15A	-	21	25	mΩ
Gate Threshold Voltage	$V_{GS(TH)}$	V_{DS}=V_{GS},I_D=250μA	1	1.8	2.5	V
Dynamic characteristics						
Gate capacitance	R_g	V_{GS}=0V,V_{DS}=0V ,f=1.0MHz	-	2.5	-	Ω
Forward Transconductance	g_{fs}	V_{DS}=10V,I_D=3A	7	-	-	S
Input Capacitance	C_{iss}	V_{DS}=40V,V_{GS}=0V f=1.0MHz	-	769	-	pF
Output Capacitance	C_{oss}		-	171	-	pF
Reverse Transfer Capacitance	C_{rss}		-	5.1	-	pF
Resistive Switching Characteristics						
Turn-on Delay Time	$t_{d(ON)}$	V_{GS}=10V, V_{DS}=50V, I_D=10A ,R_G=6Ω	-	4.3	-	ns
Rise Time	t_r		-	16.7	-	ns
Turn-off Delay Time	$t_{d(OFF)}$		-	8.7	-	ns
Fall Time	t_f		-	14.8	-	ns
Total Gate Charge	Q_g	I_D=10 A, V_{DS}=50V V_{GS}=10V	-	12.7	-	nC
Gate to Source Charge	Q_{gs}		-	2.1	-	nC
Gate to Drain("Miller") Charge	Q_{gd}		-	3.3	-	nC
Source-Drain Diode Characteristics						
Continuous Source Current(Body Diode)	I_S		-	-	40	A
Maximum Pulsed Current(Body Diode)	I_{SM}		-	-	160	A
Diode Forward Voltage	V_{SD}	I_{SD}=1A, V_{GS}=0V	-	0.75	1.2	V
Reverse Recovery Time	t_{rr}	I_{SD}=10A, T_J=25°C dI/dt=100A/μs	-	39	-	ns
Reverse Recovery Charge	Q_{rr}		-	30	-	nC

■ TYPICAL CHARACTERISTICS




Figure 1: Saturation characteristics




Figure 2: Transfer characteristics




Figure 3: $R_{DS(on)}$ vs. drain current




Figure 4: $R_{DS(on)}$ vs. junction temperature




Figure 5: Body-diode characteristics




Figure 6: Capacitance characteristics

■ TYPICAL CHARACTERISTICS(Cont.)




Figure 7: Current de-rating




Figure 8: Power de-rating




Figure 9: Maximum safe operating area

■ TO-252 PACKAGE OUTLINE DIMENSIONS

