■ PRODUCT CHARACTERISTICS

V_{DSS}	60V
$R_{DS(ON)}$Typ(@V_{GS}=10V)	4mΩ
$R_{DS(ON)}$Typ(@V_{GS}=4.5V)	5.2mΩ
I_D	90A

Symbol



■ APPLICATIONS

* High efficiency switch mode power supplies
* Electronic lamp ballasts based on half bridge
* LED power supplies



TO-252

■ FEATURE

* High Switching Speed
* Improved dv/dt capability

■ ORDER INFORMATION

Order Codes		Package	Packing
Halogen-Free	Halogen		
N/A	MOT6149D	TO-252	2500 pieces/Reel

■ ABSOLUTE MAXIMUM RATINGS(T_A=25°C,unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	60	V
Gate-Source Voltage	V_{GSS}	±20	V
Drain Current Continuous(@V_{GS}=10V ,T_A=25°C)	I_D	90	A
Drain Current Pulsed	I_{DM}	360	A
Avalanche Energy *	E_{AS}	220	mJ
Peak Diode Recovery dv/dt	dv/dt	5.0	V/ns
Power Dissipation	P_D	75	W
Junction Temperature	T_J	+150	°C
Storage Temperature	T_{STG}	-55~ +150	°C

■ THERMAL CHARACTERISTICS

Parameter	Symbol	Typ	Unit
Junction to Case	R_{thJC}	1.66	°C/W

Note: * EAS condition: T_J=25°C ,V_{DD}=25V,V_G=10V ,L=0.5mH,R_g=25Ω

■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain to Source Breakdown Voltage	V_{DSS}	V_{GS}=0V,I_D=250μA	60	-	-	V
Drain to Source Leakage Current	I_{DSS}	V_{DS}=60V,V_{GS}=0V	-	-	1	μA
Gate to Source Forward Leakage	$I_{GSS(F)}$	V_{GS}=+20V,V_{DS}=0V	-	-	100	nA
Gate to Source Reverse Leakage	$I_{GSS(R)}$	V_{GS}=-20V ,V_{DS}=0V	-	-	-100	nA
On characteristics						
Drain to Source On-Resistance	$R_{DS(ON)}$	V_{GS}=10V,I_D=20A	-	4	5.5	mΩ
		V_{GS}=4.5V,I_D=15A	-	5.2	6.7	mΩ
Gate Threshold Voltage	$V_{GS(TH)}$	V_{DS}=V_{GS},I_D=250μA	1	1.8	2.5	V
Dynamic characteristics						
Gate capacitance	R_g	V_{GS}=0V,V_{DS}=0V ,f=1.0MHz	-	1.8	-	Ω
Forward Transconductance	g_{fs}	V_{DS}=10V,I_D=3A	-	14	-	S
Input Capacitance	C_{iss}	V_{DS}=20V,V_{GS}=0V f=1.0MHz	-	2300	-	pF
Output Capacitance	C_{oss}		-	428	-	pF
Reverse Transfer Capacitance	C_{rss}		-	9.9	-	pF
Resistive Switching Characteristics						
Turn-on Delay Time	$t_{d(ON)}$	V_{GS}=10V, V_{DS}=30V, I_D=45A ,R_G=4.7Ω	-	11	-	ns
Rise Time	t_r		-	5	-	ns
Turn-off Delay Time	$t_{d(OFF)}$		-	49	-	ns
Fall Time	t_f		-	10	-	ns
Total Gate Charge	Q_g	I_D=45 A, V_{DS}=30V V_{GS}=10V	-	73	-	nC
Gate to Source Charge	Q_{gs}		-	12.5	-	nC
Gate to Drain("Miller") Charge	Q_{gd}		-	11	-	nC
Source-Drain Diode Characteristics						
Continuous Source Current(Body Diode)	I_S		-	-	90	A
Maximum Pulsed Current(Body Diode)	I_{SM}		-	-	360	A
Diode Forward Voltage	V_{SD}	I_{SD}=1A, V_{GS}=0V	-	0.71	1.2	V
Reverse Recovery Time	t_{rr}	I_{SD}=90A, T_J=25°C dI/dt=100A/μs	-	48	-	ns
Reverse Recovery Charge	Q_{rr}		-	60	-	nC

■ TYPICAL CHARACTERISTICS



Figure 1: Output Characteristics



Figure 2: Rdson-Junction Temperature



Figure 3: Transfer Characteristics



Figure 4: Gate Charge



Figure 5: Rdson-Drain Current



Figure 6: Source-Drain Diode Forward

■ TYPICAL CHARACTERISTICS(Cont.)



Figure 7: Capacitance vs Vds



Figure 8: Power De-rating



Figure 9: Safe Operation Area



Figure 10: Current De-rating

■ TO-252 PACKAGE OUTLINE DIMENSIONS

