■ PRODUCT CHARACTERISTICS

V_{DSS}	60V
$R_{DS(ON)}$ Typ(@V_{GS}=10V)	6.2mΩ
$R_{DS(ON)}$ Typ(@V_{GS}=4.5V)	8.5mΩ
I_D	85A

Symbol



■ APPLICATIONS

* High efficiency switch mode power supplies
* Electronic lamp ballasts based on half bridge
* LED power supplies



PDFN5X6

■ FEATURE

* High Switching Speed
* Improved dv/dt capability

■ ORDER INFORMATION

Order Codes		Package	Packing
Halogen-Free	Halogen		
N/A	MOT6162G	PDFN5X6	5000 pieces/Reel

■ ABSOLUTE MAXIMUM RATINGS(T_A=25°C,unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DSS}	60	V
Gate-Source Voltage	V_{GSS}	±20	V
Drain Current Continuous(@V_{GS}=10V ,T_A=25°C)	I_D	85	A
Drain Current Pulsed	I_{DM}	340	A
Avalanche Energy *	E_{AS}	210	mJ
Peak Diode Recovery dv/dt	dv/dt	5.0	V/ns
Power Dissipation	P_D	86	W
Junction Temperature	T_J	+150	°C
Storage Temperature	T_{STG}	-55~ +150	°C

■ THERMAL CHARACTERISTICS

Parameter	Symbol	Typ	Unit
Junction to Case	R_{thJC}	1.45	°C/W

Note: * EAS condition: T_J=25°C ,V_{DD}=30V,V_G=10V ,L=0.5mH,R_g=25Ω

■ ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off characteristics						
Drain to Source Breakdown Voltage	V_{DSS}	V_{GS}=0V,I_D=250μA	60	-	-	V
Drain to Source Leakage Current	I_{DSS}	V_{DS}=60V,V_{GS}=0V	-	-	1	μA
Gate to Source Forward Leakage	$I_{GSS(F)}$	V_{GS}=+20V,V_{DS}=0V	-	-	100	nA
Gate to Source Reverse Leakage	$I_{GSS(R)}$	V_{GS}=-20V ,V_{DS}=0V	-	-	-100	nA
On characteristics						
Drain to Source On-Resistance	$R_{DS(ON)}$	V_{GS}=10V,I_D=25A	-	6.2	7	mΩ
		V_{GS}=4.5V,I_D=25A	-	8.5	9.5	mΩ
Gate Threshold Voltage	$V_{GS(TH)}$	V_{DS}=V_{GS},I_D=250μA	1	1.8	2.5	V
Dynamic characteristics						
Gate Resistance	R_g	V_{GS}=0V,V_{DS}=0V ,f=1.0MHz	-	1.8	-	Ω
Forward Transconductance	g_{fs}	V_{DS}=10V,I_D=3A	10	-	-	S
Input Capacitance	C_{iss}	V_{DS}=20V,V_{GS}=0V f=1.0MHz	-	2000	-	pF
Output Capacitance	C_{oss}		-	315	-	pF
Reverse Transfer Capacitance	C_{rss}		-	9.9	-	pF
Resistive Switching Characteristics						
Turn-on Delay Time	$t_{d(ON)}$	V_{GS}=10V, V_{DS}=30V, I_D=25A ,R_G=1.6Ω	-	8	-	ns
Rise Time	t_r		-	2	-	ns
Turn-off Delay Time	$t_{d(OFF)}$		-	29	-	ns
Fall Time	t_f		-	4	-	ns
Total Gate Charge	Q_g	I_D=25 A, V_{DS}=30V V_{GS}=10V	-	26	-	nC
Gate to Source Charge	Q_{gs}		-	8.3	-	nC
Gate to Drain("Miller") Charge	Q_{gd}		-	5.5	-	nC
Source-Drain Diode Characteristics						
Continuous Source Current(Body Diode)	I_S		-	-	85	A
Maximum Pulsed Current(Body Diode)	I_{SM}		-	-	340	A
Diode Forward Voltage	V_{SD}	I_{SD}=1A, V_{GS}=0V	-	0.72	1.2	V
Reverse Recovery Time	t_{rr}	I_{SD}=25A, T_J=25°C dI/dt=100A/μs	-	38	-	ns
Reverse Recovery Charge	Q_{rr}		-	48	-	nC

■ TYPICAL CHARACTERISTICS



Figure 1 Output characteristics



Figure 2 Rdso-junction temperature



Figure 3 Transfer characteristics



Figure 4 Gate charge



Figure 5 Rdson-drain current



Figure 6 Source-drain diode forward

■ TYPICAL CHARACTERISTICS(Cont.)



Figure 7 Capacitance vs vds



Figure 8 Power de-rating



Figure 9 Safe operation area



Figure 10 Current de-rating

■ PDFN5X6 PACKAGE OUTLINE DIMENSIONS



UNIT:mm

	MIN	NOM	MAX
A	0.90	1.00	1.10
b	0.25	0.35	0.50
c	0.10	0.20	0.30
D	4.80	5.00	5.30
D1	4.90	5.10	5.50
D2	3.92	4.02	4.20
E	5.65	5.75	5.85
E1	5.90	6.05	6.20
E2	3.325	3.525	3.775
E3	0.80	0.90	1.00
e		1.27	
L	0.40	0.55	0.70
L1		0.65	
L2	0.00		0.15
K	1.00	1.30	1.50

RECOMMENDED LAND PATTERN

