



NPN型 低频放大 小功率 贴片三极管 NPN Plastic-Encapsulate Transistors SMD	S8050 对应其他工业型号
■ High breakdown voltage ■ Low collector-emitter saturation voltage ■ Transistor Polarity: NPN ■ Transistor pinout: BEC ■ SOT-23 Package ■ Marking Code: J3Y	

Inner circuit  SOT-23 内部结构	S8050B  1. Base 2. Emitter 3. Collector SOT-23 管脚排列	元件标识 (打印)  DEVICE MARKING
---	---	--

■ CLASSIFICATION OF hFE









RANK	L	H
RANGE	100~200	200~300

■ MAXIMUM RATINGS


Parameter	Symbol	Value	Unit
Collector-Base Voltage	V_{CB0}	40	V
Collector-Emitter Voltage	V_{CE0}	25	V
Emitter-Base Voltage	V_{EB0}	5	V
Collector Current	I_c	350	mA
Collector Power Dissipation	P_c	300	mW
Operation Junction and Storage Temperature Range	T_j, T_{stg}	-55~+150	°C

■ ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Characteristic	Test Condition	Symbol	Min	Typ	Max	Unit
Collector Cutoff Current	$V_{CB}=40\text{V}, I_E=0$	I_{CBO}	--	--	0.1	μA
Emitter Cutoff Current	$V_{EB}=5\text{V}, I_C=0$	I_{EBO}	--	--	0.1	μA
Collector-Base Breakdown Voltage	$I_E=0, I_C=100\mu\text{A}$	$V_{(BR)CBO}$	40	--	--	V
Collector-Emitter Breakdown Voltage	$I_E=0, I_C=10\text{mA}$	$V_{(BR)CEO}$	25	--	--	V
Emitter Cutoff Current	$I_C=0, I_E=100\mu\text{A}$	$V_{(BR)EBO}$	5	--	--	V
DC Current Gain	$I_C=100\text{mA}, V_{CE}=1\text{V}$	$h_{FE} (1)$	85	--	400	
	$I_C=350\text{mA}, V_{CE}=1\text{V}$	h_{FE}	40	--	--	
Collector-Emitter Saturation Voltage	$I_C=350\text{mA}, I_B=50\text{mA}$	$V_{CE(sat)}$	--	--	0.6	V
Base-Emitter Voltage	$V_{CE}=1\text{V}, I_C=10\text{mA}$	$V_{CE(sat)}$	--	0.8	1.0	V
Current-Gain-Bandwidth Product	$V_{CE}=5\text{V}, I_C=10\text{mA}$	f_T	100	120	--	MHz
Collector Output Capacitance	$V_{CB}=10\text{V}, I_E=0, f=1\text{MHz}$	C_{ob}	--	13	30	pF



■ DIMENSION




单位 (UNIT) : mm

序号	数值及公差
A	2.90±0.10
B	1.30±0.10
C	1.00±0.10
D	0.40±0.10
E	2.40±0.20
G	1.90±0.10
H	0.95±0.05
J	0.13±0.05
K	0.00-0.10
M	≥0.20
N	0.60±0.10
P	7±2°

Packing
SOT-23 包装规格
SMD片式表面贴封装
包装方式: 载带卷盘包装
Tape & Reel, 3Kpcs/Reel
每卷数量3000只 (3Kpcs/Reel)
每盒数量45000只 (45Kpcs/BOX)
每箱数量180000只 (180Kpcs/Cartons)


SOT-23 Tape and reel

SOT-23 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	192×192×193	180,000 pcs	404×404×214	